

100% Solids Self Leveling Moisture Cure Sealant

For Professional Use Only

DESCRIPTION

- Self-Leveling technology for all seams, fasteners, ridge caps, flashings, and penetrations.
- Moisture Curing multi-purpose one-component *paintable* sealant/adhesive.
- Adheres to all silicones
- Designed for Industrial uses requiring elasticity, high strength, and excellent adhesion.
- May be applied to surfaces at or below freezing temperatures. Make all attempts to remove frost.
- Performance at temperatures as low as -40 degrees F.
- Bonds to damp surfaces and is rain tolerant during cure.
- Cures to a Waterproof tough flexible sealant.
- Low odor and minimal shrinkage.
- Non-staining and mildew resistant.
- UV resistant.
- VOC Compliant.

RECOMMENDED USES

Industrial uses requiring high elasticity, high strength, and outstanding adhesion for a wide range of substrates. FortiSeal bonds aggressively to steel, aluminum, ceramics, spray foam, Styrofoam, EPS, glass, wood, fiberglass, concrete, silicone, and coated metals. For optimal performance we recommend coating over the material.

Property	Result
Tensile Strength:	200 psi
Elongation at break:	500%
Hardness Shore A	25 (5-day ambient cure)
Application Temperature	13 to 200 Degrees F.
Low Temp Flex	-20° F
Service Temp	-40°F to 200°F
Shelf Life (when stored @ 40°F to 80°F)	12 months

COLORS

White.

APPLICATION

Can be applied to most surfaces without primer. Typical coverage is per 1 gal. for 100 sq. ft., 1/4" Bead for 32 linear ft. or 300 fasteners. Fortiseal Pump can also be rolled using 1-1/4 inch nap roller.

PACKAGING/SHIPPING INFORMATION

CONTAINER SIZE

2 & 5 Gallon pail

SHIPPING CLASS

Class 55

To the best of our knowledge, all technical data contained herein is true and accurate as of the date of issuance and subject to change without prior notice. Users must contact Everest Systems LLC to verify correctness before specifying or ordering. We guarantee our products to conform to the quality control standards established by Everest Systems Products. We assume no responsibility for coverage, performance, or injuries resulting from use. Liability, if any, is limited to the replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY EVEREST SYSTEMS EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.